

WL800 Max II

High capacity water dispenser for demanding environments



Delivering water excellence

The WL800 Max II is designed to meet the demand for cold and hot water in high usage areas. The intuitive paddle operation and tall dispensing area enables users to easily fill large jugs and drinks bottles. The ultraviolet (UV) system maintains water hygiene in a large capacity tank and provides a continuous supply of clean and refreshing water.

Advanced technology

Two great steps to fresh water from Waterlogic®:



High performance filtration

The WL800 Max II has carbon filtration to produce the best quality drinking water. The filter removes impurities and improves taste to give you the best possible water experience.



UV sanitisation

The re-circulating UV system sanitises the water by reducing bacterial growth giving the reassurance of fresh clean drinking water.

Safe water guaranteed

The WL800 Max II professional grade UV light sanitisation system removes bacteria from the water tank without the need for toxic chemicals, so that you can enjoy refreshing great tasting water in every glass.

Features

- Cold and hot dispensing options
- Easy to clean and use faucets
- Hot water safety mechanism to protect against accidental dispensing
- Tall dispensing area designed for filling large jugs, carafes and sports bottles
- Re-circulating UV system, continuously maintains water hygiene
- High performance carbon filtration ideal for most water conditions
- Optional membrane based reverse osmosis filtration system removes the highest level of impurity and contaminants like acid, salts, nitrates, pesticides and arsenic
- Leak detection for peace of mind
- Overfill protection prevents accidental spillage

Water options

- cold 
- sparkling
- ambient
- hot 
- extra hot

Number of users

 Up to 60

Tested and certified



CE QUALITY & SAFETY
GUARANTEED

Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLI Trading Ltd licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

Technical specifications

Types available

Freestanding

Dimensions

Freestanding:
430 mm/16.9" (W) x 1250 mm/49.2" (H) x 510 mm/20.1" (D)

Dispensing area height

298 mm /11.73"

Weight

Freestanding: 43.5 kg/95 lbs

Standard filtration supplied

Carbon
Optional four stage RO (reverse osmosis) filtration

Purification system

UV lamp (4W)

Storage capacity

Room temperature: 16.8 litres/3.7 gal
Cold: 19 litres/4.2 gal
Hot: 3.5 litres/1 gal (500W heater)
Production rate: 227.3 litres/~50 gal/d (25°C/77°F, 138 kPa)

Compressor

220v/ 50Hz 110v/ 60Hz

Water temperature settings

Cold: 5°C/ 41°F
Hot: 85°C/ 185°F

Contact the export team today

Waterlogic Trading Ltd

+ 353 1 293 1960

exportsales@waterlogic.com

For more information, visit www.waterlogic.com